



FOLLOWBOT Compact 1000w LED



## DESCRIPTION

Followbot Compact 1000W LED, a hybrid LED follow spot, and its optical system can be controlled via DMX or its included mini controller. It is designed for short to midsize throw applications, the unit is a hybrid as it uses electronic motors to control most of its optical functions, yet a human still operates it. It allows integration into any application already using automated lighting to use the same theatrical DMX control to operate functions such as the color wheel, CTO wheel, built-in iris, seamless dimming, diffusion filter, zoom, and focus. Stand included.



# Features



## COMPACT

Its compact design makes this fixture easy to transport an ideal for installation with limited space.



## IDEAL FOR SHORT TO MIDSIZE APPLICATIONS

The Followbot Compact 1000W LED delivers powerful lighting in compact environments, offering reliable performance without the need for larger equipment.



## WEIGHT DISTRIBUTION YOLK

Designed to assist the operator in controlling the fixture with minimal effort by optimizing weight distribution, ensuring smoother handling and greater ease of use during operation.



## PANEL AND DMX CONTROLLABLE

This fixture can be easily controlled via its onboard panel or through DMX, offering flexibility for various setups and seamless integration into larger systems.



## 100-240V VARIABLE VOLTAGE POWER SUPPLY

Designed to operate on 100-240V power, ensuring compatibility with most electrical systems for easy integration in a variety of setups.

# Specifications.

## Mechanical Specifications:

IP Rating:	IP20
Housing:	Extruded aluminum, plastic bezel
Power connection:	Seetronics SAC3MPA Input (Nema 5-15 to SAC3FCA, Cable included)
Signal connection:	5-Pin XLR in & out
Zoom:	7° to 13°
Focus:	Electronic focus
Iris:	Electronic iris
Strobe:	Strobe control (only via DMX)
Color wheel:	Seven (7) Colors
Diffusion:	One (1) Diffusion filter
Static gogo:	One (1) Removable gobo slot (Non-rotational)
Gobo size:	39.5mm
Gobo image size:	23.5mm
Gobo max thickness:	2mm
Fastening system:	Weight distribution yolk with follow spot stand

## Control systems:

Control protocols:	Mounted scene recorder & DMX Controlled via XLR Input
Channel modes:	1 Modes of operation Mode 1: 8 Channel mode
Display:	LCD

## Electrical Specifications:

Light source:	1 X 1000W LED
Color temperature:	3 CTO Filters Open: 8537K CTO 1: 6391K CTO 2: 5336K CTO 3: 3343K
CRI (Warm white):	73
Lumen output:	Wide: 29310 Lm Narrow: 31741 Lm
Power supply:	Electronic 100-240V AC 50/60Hz
Power consumption:	1249 Watts 10.7 Amps @110V PF: 0.99

## Size and Weight:

Fixture size:	32" X 13.25" X 16.25" (81.28 cm x 33.65 cm x 41.27 cm)
Fixture weight:	63 lbs (28.5 kg)
Packaged size:	38" X 18.5" X 22.5" (96.5 cm x 46.9 cm x 57.15 cm)
Packaged weight:	66 lbs (29.9 kg)



18662 Bandera Rd  
Helotes, TX 78023

Phone (210)684-2600 / Fax (210)855-6279  
info@mega.lighting

m e g a . l i g h t i n g