




DESCRIPTION









Rated IP65 Perfect for indoor or out door events.



RGBW LEDs with 16 bit dimming for smooth color transitions.

SOURCE

· LED:

EFFECTS

· DIMMING:

· COLOR TYPE:

• WIRELESS:

· LENS:

• SEGMENT:

· SCAN RATE:

CONTROL & PROGRAMMING

· DISPLAY:

• PROTOCOL: DMX 512 13 CHANNEL MODE • DMX CHANNELS:

THERMAL & RATINGS

• MAX AMBIENT TEMP: 40°C (104°F) • MAX SURFACE TEMP: 60°C (140°F)

• IP RATING: IP65

ELECTRICAL & CONNECTIONS

• POWER CONNECTION: SEETRONIC IP CONNECTION WITH NEMA 5/15 ADAPTER

SEETRONICS IP 65 XLR 3 PIN IN/OUT · DMX CONNECTORS:

• POWER CONSUMPTION: WATTS: 272 AMPS: 2.33

RIGGING:

2 QUICK RELEASE CLAMP MOUNT 2 OR 1 POSITION • INSTALLATION SYSTEM:

Quantity: 48 Watt: 10

2 SEGMENT CONTROL

WIRELESS SOLUTIONS IP ANTENNA

16 BIT DIMMING

RGBW

7000HZ

LCD SCREEN

30°

ODERING INFO:

• OUTSHINE Q500

ACCESSORIES:

• FOUR UNIT ROAD CASE • REMOVABLE BARN DOOR

• REMOVABLE DIFFUSION FILTER **DIMENSIONS**:

• FIXTURE SIZE: 21" X 6.25" X 12.75"

PART NUMBER:

CAS-7227-4

7227-ACC-BAR


7227-ACC-DIF

7227

• FIXTURE WEIGHT: 30.75 lb

• PACKAGED SIZE: 22.5" x 8.5" x 17.5"

 PACKAGED WEIGHT: 34 lb



Photometrics:

@10ft with 30° lens

ALL LEDS ON	
Lux	2398.9
fc	222.9