
CIRCAXS



DESCRIPTION









The Circa XS Scoop LED has two unique accessories a four unit mounting frame and a seven unit mounting frame which can be used for unique lighting positions.



The Circa XS Scoop LED has independent control of dimmer, macro, and strobe along with the availability to create variable shades of white.

S	C	λ	JR	CE	=
	ı	_	_	\sim	

LED QUANTITY: · SMD LEDS WATTS:

OPTICAL SYSTEM

· LED ANGLE:

SCAN RATE:

CONTROL & PROGRAMMING

· CONTROL OPTIONS: • PROTOCOL:

• DMX CHANNELS:

THERMAL & RATINGS

• MAX AMBIENT TEMP:

• MAX SURFACE TEMP:

ELECTRICAL & CONNECTIONS

• POWER CONNECTION:

• DMX CONNECTORS:

POWER SUPPLY:

• POWER CONSUMPTION:

• FUSE: RIGGING:

• INSTALLATION SYSTEM:

MOUNTING YOKE:

84 RGB 12 WARM WHITE 45 WARM WHITE + AMBER .8W EACH

140° (OUTER RING)

7000HZ

DISPLAY CONTROL DMX 512 PROTOCOL 17 CHANNEL MODE

43°C (110°F) 60°C (140°F)

POWERCON TYPE PANEL INPUT

3 & 5 PIN XLR IN AND OUT PANEL MOUNTED ELECTRONIC AUTO SWITCHING 110V-240V 50/60HZ

WATTS: 93 AMPS: 1.30

5X20 F5AL250V

SINGLE QUICK RELEASE CLAMP MOUNT

SQUARE YOKE

ODERING INFO:

ACCESSORIES:

• REMOVABLE FLOOR BASE:

CIRCA SCOOP XS LED

SMOKE RING FILTER:

• 4 UNIT ROAD CASE: • 4 UNIT MOUNTING FRAME:

• 7 UNIT MOUNTING FRAME:

INCLUDED ITEMS:

 POWER CABLE **DIMENSIONS:**

• FIXTURE SIZE:

• FIXTURE WEIGHT:

• PACKAGED SIZE:

• PACKAGED WEIGHT:

13.5" X 7.3" X 14.12"

8 lbs

16.5" X 11" X 17"

PART NUMBER:

5199-ACC-BAS

5199-ACC-SMO


5199-ACC-7MO

5199-ACC-4MO

CAS-5199-4

5199

12 lbs



^{*}Specifications subject to change