Linebot Q480



DESCRIPTION

Create an unforgettable show with the Linebot Q480. Powered by 12 40-Watt RGBW LEDs, this bot can be used to create desired effects for a variety of applications. Featuring a broad spectrum of colors, it can produce pastel to saturated color combinations. Combined with the 12 individual pixel mapping control, the Linebot Q480 was designed to spread creativity in linear lighting. The high output LEDs can be used to produce aerial effects or highlight performers and objects on or off stage.

With a 3° to 54° zoom range, the unit offers two zoom sections for greater control. It gives the incredible ability to create piercing narrow angles that can form a harmonious curtain of light effect or wide angle wash.

The motorized 210° tilt is further enhanced with the 16 bit movement, for a seamless tilt rotation. It can be grounded or mounted using the included dual quick-release clamps. The removable side alignment guides allow multiple units to be daisy chained efficiently.

Take your show to the next level with the Linebot Q480.



The wide range of color mixing and beam effects can be enhanced with the individual pixel control of each RGBW LED.



With a 3° to 54° zoom range, the unit offers two zoom sections for greater control. The motorized 210° tilt is further enhanced with the 16 bit movement, for a seamless tilt rotation.



Equipped with 12 powerful 40-Watt RGBW LEDs to produce bright, colorful aerial effects or highlight performers and objects on or off stage.

				1
SOURCE		DIMENSIONS:		
LED TYPE:	40-Watt RGBW	FIXTURE SIZE:	40.15" X 5.12" X 11.75"	
OPTICAL SYSTEM				
LENS ANGLE:	3°-54°	 FIXTURE WEIGHT: 	38.3 lb	
EFFECTS		 PACKAGED SIZE: 	41.5" X 7.25" X 13.5"	
COLORS:	Red, Green, Blue, White	 PACKAGED WEIGHT: 	39.5 lb	
 PIXEL CONTROL: 	Individual Pixel Control of Each LED			
 ZOOM CONTROL: 	2 Independent Zoom Sections			
STROBE:	Electronic Strobe Effect With Variable Speed		·	4.33"
CONTROL & PROGRAMMING			+	→
DISPLAY:	Digital			
PROTOCOL:	DMX 512	•	•	\frown
DMX CHANNELS:	2 Modes of Operation	• •	······································	(0)
ON BOARD FEATURES:	Pre-Programmed Macros & Chase Effects at		11.75) 6 (
	Variable Speeds			MEGA
MOVEMENT			L L	
• TILT:	210° 16 Bit		•	<u> </u>
THERMAL & RATINGS	10.40 5 / 000 0			5.12"
• MAX AMBIENT TEMP:	104° F / 30° C			
MAX SURFACE TEMP:	140° F / 284° C	Q		
• MAX OPERATING TEMP:	130° F / 266° C	4		
• IP RATING:	IP20	40.15″ (W	/ith Guide)"	
ELECTRICAL & CONNECTION				
 POWER CONSUMPTION: DMX CONNCECTORS: 	Watts: 590W Amps: 5.04A 5-pin XLR In/Out			
POWER CONNECTIONS:	Seetronic Type Power In/Out			
RIGGING:	Seetionic Type Power In/Out			
INSTALLATION SYSTEM:	2 Mounting Points			
CLAMPS:	2 Quick Release Clamp Mounts			
CLAIVIFS.	2 Quick Release Clamp Mounts			
ODERING INFO:	Part Number:			
• 1 LINEBOT Q480:	1188			
ACCESSORIES:				
4 UNIT ROAD CASE	Coming Soon			
INCLUDED ITEMS:	5 5			
 1 LINEBOT Q480 				
2 QUICK RELEASE CLAMP				
MOUNTS:				
POWER CABLE				
• 1 MANUAL				

PHOTOMETRICS AT 3M

420 460 500

420 46

660 700

RED		GREEN BLUE			WHITE		ALL COLORS		
						CCT:	6958K		
LUX:	3230.2	LUX:	6251.2	LUX:	1975.5	LUX:	8604.8	LUX:	17972
WAVELENGTH (λ):	631 nm	WAVELENGTH (λ):	518 nm	WAVELENGTH (λ):	450 nm	WAVELENGTH (λ):	452 nm	WAVELENGTH (λ):	452 nm
FC:	300.2	FC:	581	FC:	183.6	FC:	799.7	FC:	1670.3
									: 0.231(: 0.178

580 620

40 580 620 660 700 740 780 λ(nm)

42

PHOTOMETRICS AT 3M (Approximately 10ft):

