Framebot



600

DESCRIPTION




The Framebot 600 is a full-featured automated luminaire with robust features packed into a medium-sized housing. This theatrical and production-grade unit is equipped with a 580W 7000K LED that produces an output of over 20,500 lumens (@ approximately 45ft). Featuring CMYK color mixing, the unit produces a broad range of pastel shades to rich saturated hues. The Colormation™ combines the effect of an animation wheel with vibrant colors that can be used to create an abstract motion effect.

With an advanced 4-blade framing system that features a 2pt pivot per blade and 180° framing rotation, the Framebot 600 allows for precise beam shaping. The impressive 6.5-42° zoom range, 540° pan and 260° tilt, enhance versatility and efficiency. The rotating 4-facet prism can be used to intensify the 6 removable rotating gobos and 7 static gobos.

This fully-loaded fixture is remarkably light for its' class weighing only 56 lbs, making it easy for transportation. Designed to be used in diverse settings, it features intelligent cooling with 3 fan noise settings that can be set from quite (52 dB) to performance (56 dB).

The Framebot 600 is the perfect multi-tool fixture to have in your lighting tool chest. The bot designed to satisfy your creativity.







The advanced 4-blade framing system with 180° framing rotation allows for precise beam shaping.



With CMYK color mixing and a 6 Color + Open wheel, the Colormation™ combines the effect of an animation wheel with vibrant colors that can be used to create an abstract motion effect.

SOURCE

· LAMP: · LED TYPE:

OPTICAL SYSTEM

ZOOM: • LUMEN: **EFFECTS**

· COLORMATION:

· COLORS: · COLOR WHEEL:

· GOBOS: • PRISM:

• FRAMING:

• FRAMING ROTATION: SOFT FILTER:

CONTROL & PROGRAMMING

· DISPLAY: · PROTOCOL: • DMX CHANNELS:

MOVEMENT • PAN: • TILT:

• PAN TILT LOCK:

THERMAL & RATINGS

• MAX AMBIENT TEMP: • MAX SURFACE TEMP: • MAX OPERATING TEMP:

• INTELLIGENT COOLING: • IP RATING:

ELECTRICAL & CONNECTIONS

• POWER CONNECTION: DMX CONNECTORS:

• POWER SUPPLY: • POWER CONSUMPTION:

RIGGING:

• INSTALLATION SYSTEM:

*Specifications subject to change

7000K **580W LED**

6.5°-42° 20,500

COLORMATION™ WHEEL

CYAN, MAGENTA, YELLOW, KELVIN (CMYK)

6 COLOR+OPEN

6 REMOVABLE ROTATING (INDEX), 7 STATIC

4 FACET PRISM LENS, ROTATABLE ADVANCED 4 BLADE FRAMING SYSTEM

INDEX OVER 180°

ADJUSTABLE SOFT FILTER

LCD SCREEN DMX 512, RDM 39 CHANNEL MODE

540° 8/16 BIT 3 PHASE STEPPER MOTOR 270° 8/16 BIT 3 PHASE STEPPER MOTOR

YES

45°C (113°F) 100°C (212°F) -5°C (23°F)

3 SETTINGS: PERFORMANCE | NORMAL | QUIET

IP20

POWERCON TYPE PANEL INPUT

3 & 5 PIN XLR IN AND OUT PANEL MOUNTED

ELECTRONIC AUTO SWITCHING 1000V-240V 50/60HZ

800W @220V

2 OMEGA CLAMP MOUNTS

ODERING INFO: PART NUMBER:

• FRAMEBOT 600 ACCESSORIES:

• 2 UNIT ROAD CASE

INCLUDED ITEMS:

• 2 QUICK RELEASE CLAMP MOUNTS

 POWER CABLE DIMENSIONS:

• FIXTURE SIZE:

14.17" X 13.31" X 25.12"

CAS11902

• FIXTURE WEIGHT: 56 lb (25 kg)

• PACKAGED SIZE: 30.5" X 18.5" X 21.5"

· PACKAGED WEIGHT: 66.2 lb (30 kg)

