N-E PIXSTRIPH216

DES CRIP TION



The N-E PIXSTRIP H216 features 18 12W LEDs that create capturing color combinations. Each LED offers individual pixel control of the Red, Green, Blue, White, Amber, and UV colors, depending on console capabilities. For ease of use, the unit features pre-programmed macros with variable speeds and chase effects that can be individually controlled. With a native 27° projection, the included diffuser softens the output and increases the angle to 105°.

Built with convectional cooling, this strip is ideal for locations requiring silent operation. With its sleek modern design, multiple fixtures can be grouped together to create an eye-catching matrix. The adjustable sliding mounts and center back mount make the unit practical and simplify the ability to create elaborate setups.

Create more lighting combinations with N-E PIXSTRIP H216!

Features.

RGBWAUV

The 18 12W LEDs offers individual pixel control of the Red, Green, Blue, White, Amber, and UV colors, depending on console capabilities.

EFFECTS

The unit features pre-programmed macros with variable speeds and chase effects that can be individually controlled. Multiple fixtures can be grouped together to create an eye-catching matrix.

FLEXIBLE MOUTING

99999

With its sleek modern design, the adjustable sliding mounts and center back mount make the unit practical and simplify the ability to create elaborate setups.

Create more lighting combinations with N-E PIXSTRIP H216!

Specifications.

Source:

Led Type: 12W LEDS

Optical System:

Led Quantity:	18
Led Angle:	27°
Diffusion Angle:	105°

Effects:

Led Colors: Pixel Protocol: RED, GREEN, BLUE, WHITE, AMBER & UV 18 PIXEL CONTROL

Control & Programing:

 Display:
 LED

 Protocol:
 DMX 512

 DMX Channels:
 3 MODES OF OPERATION

 On Board Features:
 PRE-PROGRAMMED MACROS & CHASE

 EFFECTS.

Rigging:

Installation System: DUAL SLIDING CLAMP MOUNTS

Electrical & Connections:

Power Connection:	PANEL MOUNTED SEETRONIC TYPE
	POWER IN/OUT CONNECTION.
DMX Connectors:	PANEL MOUNTED 3 & 5 PIN XLR
	CONNECTIONS IN/OUT.
Power Input:	UNIVERSAL 90-264V 50/60 HZ
Power Consumption:	126 WATTS 1.5 AMPS @ 110V

Dimensions:

Fixture Size:	39.76" X 3.94" X 5.28"
Fixture Weight:	10 lb (4.5 kg)
Packaged Size:	41" X 5.5" X 7"
Packaged Weight:	11.5 lb (5.2 kg)



18662 Bandera Rd Helotes, TX 78023

Phone (210)684-2600 / Fax (210)855-6279 info@mega.lighting

mega.lighting