


DRAMA
LED





DESCRIPTION



The Drama LED W50 is a compact yet powerful ellipsoidal with a smooth, flat spotlight. This single-source 50-watt LED fixture has a robust 2557 lumen output, yet only measures 14.5 inches long and weighs less than 5 pounds. It's just the right size for a small to medium-sized stage or venue. The Drama LED W50 has 4 lens options including 19-, 26-, 36- and 50-degree to best suit the throw requirements of the application.

Four framing blades come equipped with this unit, perfect for changing the shape of the spotlight. The fixture also comes standard with a gobo holder used to project patterns and a gel frame holder used to change the color of the spotlight. The projection can be focused manually with the unit's lens tube. Additionally, a manual iris accessory is available to adjust the diameter of the spotlight. The fixture's housing is available in black or painted white. It is manufactured with a single mounting yoke for rigging. The Drama LED W50 is an on/off lighting fixture or a controllable unit.

An external controller is available to control the fixture via DMX 512. It mounts on the side of the fixture's single yoke. This gives the unit 255 steps of dimming and a flash mode. Additionally, four dimming curves offer varying speeds of fading to black. The controller is made to your specs with either 3-pin or 5-pin DMX connections.

The unit houses an auto-switching power supply that operates from 100V to 240V.

Features.



COMPACT

This compact, powerful fixture packs a punch. At less than five pounds, this unit is easy to install and move.



MANUAL LENS

Four lens options (19°, 26°, 36°, and 50°) to best suit the application throw requirements.



DMX CONTROL

An external controller is mountable on the side of the fixture's yoke to control the Drama LED W50 via DMX 512.

**Show must
shine on**

A close-up view of a stage lighting rig. A vertical black pole is on the left, and a horizontal black pipe extends to the right. Two blue spotlights are visible, casting a strong blue glow. The background is dark, and the overall scene is dimly lit, focusing on the blue light.

Specifications.

Source

LED TYPE: 1 COB LED

Optical System

ZOOM RANGE: 15° TO 45°
LENS OPTIONS: 19°, 26°, 36°, & 50°

Effects

CRI: 84
COLOR TEMP: 5749K

Control & Programming

DISPLAY: DIGITAL
PROTOCOL: DMX 512
DMX CHANNELS: 3 MODES OF OPERATION
BALLAST: ELECTRONIC

Electrical & Connections

Power Connection: NEMA 5-15 SCREW TYPE BASE
CONNECTOR CABLE MOUNTED.
DMX Connectors: 3 OR 5-PIN XLR CONNECTORS IN AND OUT
Power Supply: UNIVERSAL 100V-240V 50/60HZ
Power Consumption: 50 WATTS | .71 AMPS

Rigging:

Installation System: SINGLE MOUNTING YOKE:

Dimensions:

Fixture Size: 12.5" X 6.33" X 5"
Fixture Weight: 3.75 lb (1.70 kg)
Packaged Size: 15" X 8" X 8"
Packaged Weight: 6 lb (2.72 kg)

MEGA **LITE**®

WWW.MEGA.LIGHTING

18662 Bandera Rd
Helotes, TX 78023

Phone (210)684-2600 / Fax (210)855-6279
info@mega.lighting

m e g a . l i g h t i n g