



DES CRIP TION



Designed to seamlessly control our Light Pipe and Tetra Series units, this all-in-one solution has 4 outputs that can be individually addressed within your preferred channel mode.

To further enhance versatility, this powerful driver features multiple mounting points, allowing for easy wall mounting and clamp mounting.

For easy production and installation implementation.

Features.




FOUR 96W OUTPUTS

The unit is equipped with four 96W outputs. Each port can connect up to 96W of power. When using our Light Pipe series you can create many different combinations of lengths.



WIRELESS DMX

Using this function allows you to wirelessly control your DMX connected fixtures using a wireless DMX Connection.



IP65

Resistant to water and protected from dust, this unit is perfect for outdoor venues and events.

Specifications.

Mechanical Specifications

IP Rating:

65

Housing: Fastening

Aluminum Extrusion

System:

M10 Clamp Mount Thread, Mounting Holes, Accessory DIN Rail Mounts.

Power Connection:

Seetronics SAC3FX IP-Rated Connection (Nema 5-15 Cable Included).

DMX Connection:
Wireless DMX Connection:

5-Pin XLR In and Out Lumen Radio Wireless DMX

Connection Receiver

Output Connection:

Four (4) 5-Pin XLR Outputs

Electrical Specifications

Output Ports: Four (4)

Power Per Port: 96W
Drive Method: Constant Voltage

Power Consumption: 3.18 Amps

376 Watts.

Power Supply: Electronic: Mean Well UHP-500-24

Output: 24V DC
Working Ambient Temp: 24 °F - 148 °F
Cooling: Internal Fan
Refresh: 4.000Hz

Power Input: 90-264V AC 50/60Hz

Control Systems

Control Protocols:

DMX 512

Operating Mode: DMX 5 Modes:

17 Pre-Programs Manual
1 Channel Mode Dimmer

Manual Settings Via Display

2 Channel Mode Warm

Warm White, Cool White

3 Channel Mode

R,G,B

4 Channel Mode

R, G, B, W

7 Channel Mode

Dimmer, R, G, B, W, Strobe, Macro

Size and Weight

Fixture Size: 13.25" X 9.5" X 4.12"

Fixture Weight: 8.8 lbs

Packaged Size: 14.75" x 12" x 6.75"

Packaged Weight: 9.8 lbs



18662 Bandera Rd Helotes, TX 78023

Phone (210)684-2600 / Fax (210)855-6279 info@mega.lighting